



HONEY BROOKE

SPECIFICATIONS

THIN VENEER FULL VENEER bimobject

	ORIGIN	MOSINEE, WISCONSIN (SANDSTONE)
	INFO	75% SPLITFACE, 25% SNAPPED BEDFACE
	PATTERN	NATURAL COURSE, RANDOM ASHLAR
	COLOR	CREAM, LIGHT TAN, BROWN, SOME HORIZONTAL STRIPING
	AREA	37-40 SQFT / TON (FULL) 12-15 LBS/SQFT (THIN)
	HEIGHT	RANDOM 2" - 6" JUMPERS 6" - 9" SNAPPED BF @ 8" AND 10" (+/- 1)
	LENGTH	6" - 36" THIN VENEER CORNERS: 6"-13"
	WIDTH	FULL: 3"-5" (4") THIN: 3/4"-1 1/2"
	DENSITY	152 LB/FT ³



ASTM - C170

COMPRESSIVE STRENGTH

18,360 PSI	PERPENDICULAR TO RIFT, WET
17,510 PSI	PERPENDICULAR TO RIFT, DRY
15,300 PSI	PARALLEL TO RIFT, WET
16,530 PSI	PARALLEL TO RIFT, DRY

ASTM - C97

ABSORPTION & SPECIFIC GRAVITY

1.04%	WATER ABSORPTION
2.44	BULK SPECIFIC GRAVITY

ASTM - C880

FLEXURAL STRENGTH

460 PSI	AVERAGE FLEXURAL STRENGTH, WET
480 PSI	AVERAGE FLEXURAL STRENGTH, DRY

