

OAKFIELD STONEGATE - RED

SPECIFICATIONS

THIN VENEER FULL VENEER **bimobject**



ORIGIN

OAKFIELD, WISCONSIN



INFO

100% SPLITFACE - MACHINE CUT



PATTERN

NATURAL COURSE, RANDOM ASHLAR



COLOR

BEIGE, MAROON, DARK REDDISH-PURPLE
 SPLITFACE



AREA

37-40 SQFT / TON (FULL) 12-15 LBS/SQFT
 (THIN)



HEIGHT

RANDOM 2" - 6"



LENGTH

6" - 28" THIN VENEER CORNERS: 6"-13"



WIDTH

FULL: 3"-5" (4") THIN: 3/4"-1/2"



DENSITY

176 LB/FT³ (OAK)



ASTM - C170

COMPRESSIVE STRENGTH

24,740 PSI	PERPENDICULAR TO RIFT, WET
31,490 PSI	PERPENDICULAR TO RIFT, DRY
27,060 PSI	PARALLEL TO RIFT, WET
25,060 PSI	PARALLEL TO RIFT, DRY

ASTM - C97

ABSORPTION & SPECIFIC GRAVITY

.29%	WATER ABSORPTION
2.81	BULK SPECIFIC GRAVITY

ASTM - C880

FLEXURAL STRENGTH

1,010 PSI	AVERAGE FLEXURAL STRENGTH, WET
1,020 PSI	AVERAGE FLEXURAL STRENGTH, DRY

