










PRAIRIE NIAGARA LEDGE

SPECIFICATIONS

THIN VENEER FULL VENEER bimobject

	ORIGIN	BEAVER DAM, WISCONSIN
	INFO	BEDFACE DIMENSIONAL
	PATTERN	SAWN DIMENSIONAL, ASHLAR
	COLOR	GOLD, BROWN, TAN
	AREA	37-40 SQFT / TON (FULL) 12-15 LBS/SQFT (THIN)
	HEIGHT	SAWN 2-1/4", 5", 7-3/4", 10-1/2"
	LENGTH	6" - 42" THIN VENEER CORNERS: 6"-13"
	WIDTH	FULL: 3"-5" (4") THIN: 3/4"-1/2"
	DENSITY	173 LB/FT ³



ASTM - C170

COMPRESSIVE STRENGTH

24,970 PSI	PERPENDICULAR TO RIFT, WET
26,360 PSI	PERPENDICULAR TO RIFT, DRY
25,110 PSI	PARALLEL TO RIFT, WET
29,220 PSI	PARALLEL TO RIFT, DRY

ASTM - C97 ABSORPTION & SPECIFIC GRAVITY

0.57%	WATER ABSORPTION
2.76	BULK SPECIFIC GRAVITY

ASTM - C880 FLEXURAL STRENGTH

1,100 - 1,260 PSI	AVERAGE FLEXURAL STRENGTH, WET
1,430 - 1,590 PSI	AVERAGE FLEXURAL STRENGTH, DRY

