

CHILTON COTTAGE MANOR

SPECIFICATIONS

THIN VENEER ☒ FULL VENEER ☒ bimobject ☒



ORIGIN

CHILTON, WISCONSIN



INFO

SPLITFACE, RUSTIC WEATHEREDGE,
SNAPPED BEDFACE
(STONEGATE, RUSTIC ANTIQUE, CASTLE
RIDGE)



PATTERN

NATURAL COURSE, RANDOM ASHLAR



COLOR

GRAY, SILVER, DARK GRAY-BLUE, MAUVE,
RED, GOLD, GREEN-BLUE, PURPLE
BEDFACE



AREA

37 SQFT / TON (FULL) 13-15 LBS/SQFT (THIN)



HEIGHT

SPLITFACE 2" - 6", OPTIONAL JUMPERS 6"-
9", SNAPPED BEDFACE 8", 10" (+/- 1")



LENGTH

RANDOM 6" - 30" THIN VENEER CORNERS:
6"-13"



WIDTH

FULL: 3"-5" (4") THIN: 3/4" - 1-1/2"



DENSITY

167.1 LB/FT³



ASTM - C170

COMPRESSIVE STRENGTH

30,850 PSI	PERPENDICULAR TO RIFT, WET
21,560 PSI	PERPENDICULAR TO RIFT, DRY
25,930 PSI	PARALLEL TO RIFT, WET
29,010 PSI	PARALLEL TO RIFT, DRY

ASTM - C97

ABSORPTION & SPECIFIC GRAVITY

CHILTON: .95%	WATER ABSORPTION
CHILTON: 2.676	BULK SPECIFIC GRAVITY

ASTM - C99

MODULUS OF RUPTURE

1,650 PSI - 2,130 PSI	MODULUS OF RUPTURE, WET
1,800 PSI - 2,420 PSI	MODULUS OF RUPTURE, DRY