

SPECIFICATIONS

THIN VENEER ☒ FULL VENEER ☒



ORIGIN

OAKFIELD, WISCONSIN



INFO

100% COLORED SEAMFACE, MACHINE CUT



PATTERN

NATURAL, RANDOM ASHLAR



COLOR

GOLDS, YELLOWS, RUSTIC TONES



AREA

35-37 SQFT / TON (FULL) 12-15 LBS/SQFT (THIN)



HEIGHT

RANDOM 2" - 6"



LENGTH

6" - 24" THIN VENEER CORNERS: 6" - 13"



WIDTH

FULL: 3" - 5" (4") THIN: 3/4" - 1 1/2"



DENSITY

176 LB/FT³



ASTM - C170

COMPRESSIVE STRENGTH 

24,740 PSI PERPENDICULAR TO RIFT, WET

31,490 PSI PERPENDICULAR TO RIFT, DRY

27,060 PSI PARALLEL TO RIFT, WET

25,060 PSI PARALLEL TO RIFT, DRY

ASTM - C97

ABSORPTION & SPECIFIC GRAVITY 

.29% WATER ABSORPTION

2.81 BULK SPECIFIC GRAVITY

ASTM - C880

FLEXURAL STRENGTH 

1,100 PSI AVERAGE FLEXURAL STRENGTH, WET

1,020 PSI AVERAGE FLEXURAL STRENGTH, DRY

