










OAKFIELD CASTLE RIDGE

SPECIFICATIONS

THIN VENEER FULL VENEER

	ORIGIN	OAKFIELD, WISCONSIN
	INFO	100% SNAPPED BEDFACE
	PATTERN	ROUGH COURSE, ASHLAR
	COLOR	GOLD, BROWN, TAN, BEIGE, EARTH TONES
	AREA	37 SQFT / TON (FULL) 12-15 LBS/SQFT (THIN)
	HEIGHT	SNAPPED 4", 6", 8", 10", 12" (+/- 1")
	LENGTH	6" - 30" THIN VENEER CORNERS: 6"-13"
	WIDTH	FULL: 3"-5" (4") THIN: 3/4"- 1/2"
	DENSITY	176 LB/FT ³



ASTM - C170

COMPRESSIVE STRENGTH

24,740 PSI	PERPENDICULAR TO RIFT, WET
31,490 PSI	PERPENDICULAR TO RIFT, DRY
27,060 PSI	PARALLEL TO RIFT, WET
25,060 PSI	PARALLEL TO RIFT, DRY

ASTM - C97 ABSORPTION & SPECIFIC GRAVITY

.29%	WATER ABSORPTION
2.81	BULK SPECIFIC GRAVITY

ASTM - C880

FLEXURAL STRENGTH

1,000 PSI	AVERAGE FLEXURAL STRENGTH, WET
1,020 PSI	AVERAGE FLEXURAL STRENGTH, DRY