




## SPECIFICATIONS

THIN VENEER  FULL VENEER  bimobject

	ORIGIN	OAKFIELD, WISCONSIN
	INFO	100% SPLITFACE, MACHINE CUT
	PATTERN	NATURAL, RANDOM ASHLAR
	COLOR	GRAY / BEIGE WITH GOLDS, TANS, AND EARTHY TONES
	AREA	40 SQFT / TON (FULL) 12-15 LBS/SQFT (THIN)
	HEIGHT	RANDOM 2" - 6"
	LENGTH	6" - 24" THIN VENEER CORNERS: 6"-13"
	WIDTH	FULL: 3"-5" (4") THIN: 3/4"-1 1/2"
	DENSITY	176 LB/FT <sup>3</sup>



### ASTM - C170

### COMPRESSIVE STRENGTH

24,740 PSI	PERPENDICULAR TO RIFT, WET
31,490 PSI	PERPENDICULAR TO RIFT, DRY
27,060 PSI	PARALLEL TO RIFT, WET
25,060 PSI	PARALLEL TO RIFT, DRY

### ASTM - C97 ABSORPTION & SPECIFIC GRAVITY

29%	WATER ABSORPTION
2.81	BULK SPECIFIC GRAVITY

### ASTM - C880 FLEXURAL STRENGTH

1,010 PSI	AVERAGE FLEXURAL STRENGTH, WET
1,020 PSI	AVERAGE FLEXURAL STRENGTH, DRY

